



Clam AntiVirus 0.91rc1
User Manual

Contents

1	Introduction	3
1.1	Features	3
1.2	Mailing lists and IRC channel	4
1.3	Virus submitting	5
2	Base package	5
2.1	Supported platforms	5
2.2	Binary packages	5
3	Installation	6
3.1	Requirements	6
3.2	Installing on shell account	6
3.3	Adding new system user and group	7
3.4	Compilation of base package	7
3.5	Compilation with clamav-milter enabled	7
4	Configuration	8
4.1	clamd	8
4.1.1	On-access scanning	8
4.2	clamav-milter	9
4.3	Testing	9
4.4	Setting up auto-updating	10
4.4.1	Closest mirrors	11
5	Usage	11
5.1	Clam daemon	11
5.2	Clamscan	12
5.3	Clamuko	13
5.4	Output format	13
5.4.1	clamscan	13
5.4.2	clamd	14
6	LibClamAV	15
6.1	Licence	15
6.2	Supported formats	15
6.2.1	Executables	15
6.2.2	Mail files	16
6.2.3	Archives and compressed files	16

6.2.4	Documents	16
6.2.5	Others	17
6.3	Hardware acceleration	17
6.4	API	17
6.4.1	Header file	17
6.4.2	Database loading	17
6.4.3	Error handling	18
6.4.4	Engine structure	19
6.5	Database reloading	19
6.5.1	Data scan functions	20
6.5.2	Memory	22
6.5.3	clamav-config	22
6.5.4	Example	23
6.6	CVD format	23
6.7	Contributors	23
6.8	Donors	34
6.9	Graphics	40
6.10	OpenAntiVirus	40
7	Core Team	40

ClamAV User Manual, © 2002 - 2007 Tomasz Kojm

This document is distributed under the terms of the GNU General Public License v2.

Clam AntiVirus is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with this program; if not, write to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

ClamAV and Clam AntiVirus are trademarks of Tomasz Kojm.

1 Introduction

Clam AntiVirus is an anti-virus toolkit for UNIX, designed especially for e-mail scanning on mail gateways. It provides a number of utilities including a flexible and scalable multi-threaded daemon, a command line scanner and advanced tool for automatic database updates. The core of the package is an anti-virus engine available in a form of shared library.

1.1 Features

- Licensed under the GNU General Public License, Version 2
- POSIX compliant, portable
- Fast scanning
- Supports on-access scanning (Linux and FreeBSD only)
- Detects over 120.000 viruses, worms and trojans, including Microsoft Office macro viruses, mobile malware, and other threats
- Scans within archives and compressed files (also protects against archive bombs), built-in support includes:
 - Zip (including SFX)
 - RAR (including SFX)
 - Tar
 - Gzip
 - Bzip2
 - MS OLE2
 - MS Cabinet Files (including SFX)
 - MS CHM (Compiled HTML)
 - MS SZDD compression format
 - BinHex
 - SIS (SymbianOS packages)
- Supports Portable Executable (32/64-bit) files compressed or obfuscated with:
 - UPX
 - FSG

- Petite
 - NsPack
 - wwpack32
 - MEW
 - Upack
 - SUE
 - Y0da Cryptor
- Supports almost all mail file formats
- Support for other special files/formats includes:
 - HTML
 - RTF
 - PDF
 - Files encrypted with CryptFF and ScrEnc
 - uuencode
 - TNEF (winmail.dat)
- Advanced database updater with support for scripted updates, digital signatures and DNS based database version queries

1.2 Mailing lists and IRC channel

If you have a trouble installing or using ClamAV try asking on our mailing lists. There are four lists available:

- **clamav-announce*lists.clamav.net** - info about new versions, moderated¹.
- **clamav-users*lists.clamav.net** - user questions
- **clamav-devel*lists.clamav.net** - technical discussions
- **clamav-virusdb*lists.clamav.net** - database update announcements, moderated

You can subscribe and search the mailing list archives at: <http://www.clamav.net/support/ml/>

Alternatively you can try asking on the #clamav IRC channel - launch your favourite irc client and type:

¹Subscribers are not allowed to post to the mailing list

```
/server irc.freenode.net  
/join #clamav
```

1.3 Virus submitting

If you have got a virus which is not detected by your ClamAV with the latest databases, please submit the sample at our website:

<http://www.clamav.net/sendvirus>

2 Base package

2.1 Supported platforms

Most popular UNIX operating systems are supported. Clam AntiVirus 0.90 was tested on:

- GNU/Linux
- Solaris
- FreeBSD
- OpenBSD ²
- Mac OS X

Some features may not be available on your operating system. If you are successfully running Clam AntiVirus on a system not listed above please let us know.

2.2 Binary packages

You can find the up-to-date list of binary packages at our website: <http://www.clamav.net/download/packages/>

²Installation from a port is recommended.

3 Installation

3.1 Requirements

The following elements are required to compile ClamAV:

- zlib and zlib-devel packages
- gcc compiler suite (tested with 2.9x, 3.x and 4.x series)

The following packages are optional but **highly recommended**:

- bzip2 and bzip2-devel library
- GNU MP 3

It's very important to install the GMP package because it allows `freshclam` to verify the digital signatures of the virus databases and scripted updates. If `freshclam` was compiled without GMP support it will display "SECURITY WARNING: NO SUPPORT FOR DIGITAL SIGNATURES" on every update. You can download GNU MP at <http://www.swox.com/gmp/>

A note for Solaris/SPARC users: you must set the *ABI* system variable to 32 (e.g. `setenv ABI 32`) before running the configuration script of GMP.

3.2 Installing on shell account

To install ClamAV locally on an unprivileged shell account you need not create any additional users or groups. Assuming your home directory is `/home/gary` you should build it as follows:

```
$ ./configure --prefix=/home/gary/clamav --disable-clamav
$ make; make install
```

To test your installation execute:

```
$ ~/clamav/bin/freshclam
$ ~/clamav/bin/clamscan ~
```

The `--disable-clamav` switch disables the check for existence of the `clamav` user and group but `clamscan` would still require an unprivileged account to work in a superuser mode.

3.3 Adding new system user and group

If you are installing ClamAV for the first time, you have to add a new user and group to your system: ³

```
# groupadd clamav
# useradd -g clamav -s /bin/false -c "Clam AntiVirus" clamav
```

Consult a system manual if your OS has not *groupadd* and *useradd* utilities. **Don't forget to lock access to the account!**

3.4 Compilation of base package

Once you have created the clamav user and group, please extract the archive:

```
$ zcat clamav-x.yz.tar.gz | tar xvf -
$ cd clamav-x.yz
```

Assuming you want to install the configuration files in /etc, configure and build the software as follows:

```
$ ./configure --sysconfdir=/etc
$ make
$ su -c "make install"
```

In the last step the software is installed into the /usr/local directory and the config files into /etc. **WARNING: Never enable the SUID or SGID bits for Clam AntiVirus binaries.**

3.5 Compilation with clamav-milter enabled

libmilter and its development files are required. To enable clamav-milter, configure ClamAV with

```
$ ./configure --enable-milter
```

³Cygwin note: If you have not /etc/passwd you can skip this point

4 Configuration

4.1 clamd

Before you start using the daemon you have to edit the configuration file (in other case clamd won't run):

```
$ clamd
ERROR: Please edit the example config file /etc/clamd.conf.
```

This shows the location of the default configuration file. The format and options of this file are fully described in the *clamd.conf(5)* manual. The config file is well commented and configuration should be straightforward.

4.1.1 On-access scanning

One of the interesting features of clamd is on-access scanning based on the Dazuko module, available from <http://dazuko.org/>. **This module is not required to run clamd - furthermore, you shouldn't run Dazuko on production systems.** At the moment Dazuko is available for Linux and FreeBSD, but the following information only covers Linux.

```
$ tar xpvf dazuko-a.b.c.tar.gz
$ cd dazuko-a.b.c
$ make dazuko
or
$ make dazuko-smp (for smp kernels)
$ su
# insmod dazuko.o
# cp dazuko.o /lib/modules/`uname -r`/misc
# depmod -a
```

Depending on your Linux distribution you may need to add a "dazuko" entry to */etc/modules* or run the module during system's startup by adding

```
/sbin/modprobe dazuko
```

to some startup file. You must also create a new device:

```
$ cat /proc/devices | grep dazuko
254 dazuko
$ su -c "mknod -m 600 /dev/dazuko c 254 0"
```

Now configure Clamuko in `clamd.conf` and read the 5.3 section.

4.2 clamav-milter

Nigel Horne's `clamav-milter` is a very efficient email scanner designed for Sendmail. It's written entirely in C and only depends on `libclamav` or `clamd`. You can find detailed installation instructions in the `INSTALL` file that comes with the `clamav-milter` sources. Basically, to connect it with Sendmail add the following lines to `/etc/mail/sendmail.mc`:

```
INPUT_MAIL_FILTER(`clmilter', `S=local:/var/run/clamav/clmilter.sock,
F=, T=S:4m;R:4m')dnl
define(`confINPUT_MAIL_FILTERS', `clmilter')
```

If you're running it in `--external` mode, check entry in `clamd.conf` of the form:

```
LocalSocket /var/run/clamav/clamd.sock
```

Start `clamav-milter`

```
/usr/local/sbin/clamav-milter -lo /var/run/clamav/clmilter.sock
```

and restart sendmail.

4.3 Testing

Try to scan recursively the source directory:

```
$ clamscan -r -l scan.txt clamav-x.yz
```

It should find some test files in the `clamav-x.yz/test` directory. The scan result will be saved in the `scan.txt` log file⁴. To test `clamd`, start it and use `clamdsan` (or instead connect directly to its socket and run the `SCAN` command):

```
$ clamdsan -l scan.txt clamav-x.yz
```

Please note that the scanned files must be accessible by the user running `clamd` or you will get an error.

⁴To get more info on `clamscan` options run `'man clamscan'`

4.4 Setting up auto-updating

`freshclam` is the automatic database update tool for Clam AntiVirus. It can work in two modes:

- interactive - on demand from command line
- daemon - silently in the background

`freshclam` is advanced tool: it supports scripted updates (instead of transferring the whole CVD file at each update it only transfers the differences between the latest and the current database via a special script), database version checks through DNS, proxy servers (with authentication), digital signatures and various error scenarios. **Quick test: run `freshclam` (as superuser) with no parameters and check the output.** If everything is OK you may create the log file in `/var/log` (owned by `clamav` or another user `freshclam` will be running as):

```
# touch /var/log/freshclam.log
# chmod 600 /var/log/freshclam.log
# chown clamav /var/log/freshclam.log
```

Now you *should* edit the configuration file `freshclam.conf` and point the *UpdateLogFile* directive to the log file. Finally, to run `freshclam` in the daemon mode, execute:

```
# freshclam -d
```

The other way is to use the *cron* daemon. You have to add the following line to the crontab of **root** or **clamav** user:

```
N * * * * /usr/local/bin/freshclam --quiet
```

to check for a new database every hour. **N should be a number between 3 and 57 of your choice. Please don't choose any multiple of 10, because there are already too many clients using those time slots.** Proxy settings are only configurable via the configuration file and `freshclam` will require strict permission settings for the config file when `HTTPProxyPassword` is turned on.

```
HTTPProxyServer myproxyserver.com
HTTPProxyPort 1234
HTTPProxyUsername myusername
HTTPProxyPassword mypass
```

4.4.1 Closest mirrors

The `DatabaseMirror` directive in the config file specifies the database server `freshclam` will attempt (up to `MaxAttempts` times) to download the database from. The default database mirror is `database.clamav.net` but multiple directives are allowed. In order to download the database from the closest mirror you should configure `freshclam` to use `db.xx.clamav.net` where `xx` represents your country code. For example, if your server is in "Ascension Island" you should have the following lines included in `freshclam.conf`:

```
DNSDatabaseInfo current.cvd.clamav.net
DatabaseMirror db.ac.clamav.net
DatabaseMirror database.clamav.net
```

The second entry acts as a fallback in case the connection to the first mirror fails for some reason. The full list of two-letters country codes is available at <http://www.iana.org/cctld/cctld-whois.htm>

5 Usage

5.1 Clam daemon

`clamd` is a multi-threaded daemon that uses *libclamav* to scan files for viruses. It may work in one or both modes listening on:

- Unix (local) socket
- TCP socket

The daemon is fully configurable via the `clamd.conf` file ⁵. `clamd` recognizes the following commands:

- **PING**
Check the daemon's state (should reply with "PONG").
- **VERSION**
Print program and database versions.
- **RELOAD**
Reload the databases.

⁵man 5 clamd.conf

- **SHUTDOWN**
Perform a clean exit.
- **SCAN file/directory**
Scan file or directory (recursively) with archive support enabled (a full path is required).
- **RAWSCAN file/directory**
Scan file or directory (recursively) with archive and special file support disabled (a full path is required).
- **CONTSCAN file/directory**
Scan file or directory (recursively) with archive support enabled and don't stop the scanning when a virus is found.
- **MULTISCAN file/directory**
Scan file in a standard way or scan directory (recursively) using multiple threads (to make the scanning faster on SMP machines).
- **STREAM**
Scan stream: `clamd` will return a new port number you should connect to and send data to scan.
- **SESSION, END**
Start/end a `clamd` session - you can do multiple commands per TCP session (WARNING: due to the `clamd` implementation the **RELOAD** command will break the session).

and reacts on the special signals:

- **SIGTERM** - perform a clean exit
- **SIGHUP** - reopen the log file
- **SIGUSR2** - reload the database

5.2 Clamscan

`clamscan` is a simple `clamd` client. In many cases you can use it as a `clamscan` replacement however you must remember that:

- it only depends on `clamd`
- although it accepts the same command line options as `clamscan` most of them are ignored because they must be enabled directly in `clamd`, i.e. `clamd.conf`

- scanned files must be accessible for `clamd`
- it can't use external unpackers

5.3 Clamuko

Clamuko is a special thread in `clamd` that performs on-access scanning under Linux and FreeBSD and shares internal virus database with the daemon. **You must follow some important rules when using it:**

- Always stop the daemon cleanly - using the SHUTDOWN command or the SIGTERM signal. In other case you can lose access to protected files until the system is restarted.
- Never protect the directory your mail-scanner software uses for attachment unpacking. Access to all infected files will be automatically blocked and the scanner (including `clamd`!) will not be able to detect any viruses. In the result **all infected mails may be delivered.**

For example, to protect the whole system add the following lines to `clamd.conf`:

```
ClamukoScanOnAccess
ClamukoIncludePath /
ClamukoExcludePath /proc
ClamukoExcludePath /temporary/dir/of/your/mail/scanning/software
```

You can also use clamuko to protect files on Samba/Netatalk but a far more better and safe idea is to use the **samba-vscan** module. NFS is not supported because Dazuko doesn't intercept NFS access calls.

5.4 Output format

5.4.1 clamscan

`clamscan` writes all regular program messages to **stdout** and errors/warnings to **stderr**. You can use the option `--stdout` to redirect all program messages to **stdout**. Warnings and error messages from `libclamav` are always printed to **stderr**. A typical output from `clamscan` looks like this:

```
/tmp/test/removal-tool.exe: Worm.Sober FOUND
/tmp/test/md5.o: OK
/tmp/test/blob.c: OK
```

```
/tmp/test/message.c: OK
/tmp/test/error.hta: VBS.Inor.D FOUND
```

When a virus is found its name is printed between the `filename:` and `FOUND` strings. In case of archives the scanner depends on `libclamav` and only prints the first virus found within an archive:

```
zolw@localhost:/tmp$ clamscan malware.zip
malware.zip: Worm.Mydoom.U FOUND
```

TIP: You can force `clamscan` to list all infected files in an archive using `-no-archive` (this option disables transparent decompressors built into `libclamav`) and enabling external decompressors: `-unzip -unrar...`

```
zolw@localhost:/tmp$ clamscan --no-archive --unzip malware.zip
Archive: /tmp/malware.zip
  inflating: test1.exe
  inflating: test2.exe
  inflating: test3.exe
/tmp/clamav-77e7bfd3872b/test1.exe: Worm.Mydoom.U FOUND
/tmp/clamav-77e7bfd3872b/test2.exe: Trojan.Taskkill.A FOUND
/tmp/clamav-77e7bfd3872b/test3.exe: Worm.Nyxem.D FOUND
/tmp/malware.zip: Infected.Archive FOUND
```

5.4.2 clamd

The output format of `clamd` is very similar to `clamscan`.

```
zolw@localhost:~$ telnet localhost 3310
Trying 127.0.0.1...
Connected to localhost.
Escape character is '^]'.
SCAN /home/zolw/test
/home/zolw/test/clam.exe: ClamAV-Test-File FOUND
Connection closed by foreign host.
```

In the **SCAN** mode it closes the connection when the first virus is found.

```
SCAN /home/zolw/test/clam.zip  
/home/zolw/test/clam.zip: ClamAV-Test-File FOUND
```

CONTSCAN and **MULTISCAN** don't stop scanning in case a virus is found. Error messages are printed in the following format:

```
SCAN /no/such/file  
/no/such/file: Can't stat() the file. ERROR
```

6 LibClamAV

Libclamav provides an easy and effective way to add a virus protection into your software. The library is thread-safe and transparently recognizes and scans within archives, mail files, MS Office document files, executables and other special formats.

6.1 Licence

Libclamav is licensed under the GNU GPL v2 licence. This means you are **not allowed** to link commercial, close-source applications against it⁶. All software using libclamav must be GPL compliant.

6.2 Supported formats

6.2.1 Executables

The library has a built-in support for 32/64-bit Portable Executable files and 32-bit ELF files. Additionally, it can handle PE files compressed or obfuscated with the following tools:

- UPX (all versions)
- FSG (1.3, 1.31, 1.33, 2.0)
- Petite (2.x)
- NsPack
- wwpack32 (1.20)

⁶You can still use clamd or clamscan instead

- MEW
- Upack
- SUE
- Y0da Cryptor (1.3)

6.2.2 Mail files

Libclamav can handle almost every mail file format including TNEF (winmail.dat) attachments.

6.2.3 Archives and compressed files

The following archive and compression formats are supported by internal handlers:

- Zip (+ SFX)
- RAR (+ SFX)
- Tar
- Gzip
- Bzip2
- MS OLE2
- MS Cabinet Files (+ SFX)
- MS CHM (Compiled HTML)
- MS SZDD compression format
- BinHex
- SIS (SymbianOS packages)

6.2.4 Documents

The most popular file formats are supported:

- MS Office and MacOffice files
- RTF
- PDF
- HTML

6.2.5 Others

Libclamav can handle various obfuscators, encoders, files vulnerable to security risks such as:

- JPEG (exploit detection)
- RIFF (exploit detection)
- uuencode
- ScrEnc obfuscation
- CryptFF

6.3 Hardware acceleration

ClamAV 0.90 comes with support for Sensory Networks' NodalCore acceleration technology. Thanks to specialized Security Processing Unit built into NodalCore C-Series accelerators it is possible to achieve more performance than is possible by just adding general purpose CPUs. Additionally, Sensory Networks' CorePAKT technology ensures that compiled signature databases occupy a memory footprint smaller than any other competing technology on the market - in many cases by up to 90%. The ability to store multiple databases in compressed format whilst still achieving high throughputs makes NodalCore ideal for applications demanding high performance on large signature databases such as ClamAV.

For more information please visit <http://www.clamav.net/nodalcore/>

6.4 API

6.4.1 Header file

Every program using libclamav must include the header file `clamav.h`:

```
#include <clamav.h>
```

6.4.2 Database loading

The following set of functions provides an interface for loading the virus database:

```
const char *cl_retdbdir(void);

int cl_load(const char *path, struct cl_engine **engine,
```

```
unsigned int *signo, unsigned int options);
```

`cl_retdbdir` returns the default (hardcoded) path to the directory with ClamAV databases. `cl_load` loads a single database file or all databases from a directory (if `path` points to a directory). The second argument is used for passing in the engine structure which should be previously initialized with `NULL`. A number of loaded signatures will be **added** to `signo`⁷. The last argument can pass the following flags:

- **CL_DB_STDOPT**
This is an alias for a recommended set of scan options.
- **CL_DB_NCORE**
Initialize NodalCore and load the hardware database (if applicable).
- **CL_DB_PHISHING**
Load phishing signatures.
- **CL_DB_PHISHING_URLS**
Initialize the phishing detection module and load `.wdb` and `.pdb` files.

`cl_load` returns 0 (`CL_SUCCESS`) on success and a non-negative value on failure.

```
...
struct cl_engine *engine = NULL;
unsigned int sigs = 0;
int ret;
```

```
ret = cl_load(cl_retdbdir(), &engine, &sigs, CL_DB_STDOPT);
```

6.4.3 Error handling

Use `cl_strerror` to convert error codes into human readable messages. The function returns a statically allocated string:

```
if(ret) {
    printf("cl_load() error: %s\n", cl_strerror(ret));
    exit(1);
}
```

⁷Remember to initialize the virus counter variable with 0.

6.4.4 Engine structure

When all required databases are loaded you should prepare the detection engine by calling `cl_build`. In the case of failure you should free the memory occupied by the engine with `cl_free`:

```
int cl_build(struct cl_engine *engine);
void cl_free(struct cl_engine *engine);
```

In our example:

```
if((ret = cl_build(engine))) {
    printf("cl_build() error: %s\n", cl_strerror(ret));
    cl_free(engine);
    exit(1);
}
```

6.5 Database reloading

The most important thing is to keep the internal instance of the database up to date. You can watch database changes with the `cl_stat` family of functions.

```
int cl_statinidir(const char *dirname, struct cl_stat *dbstat);
int cl_statchkdir(const struct cl_stat *dbstat);
int cl_statfree(struct cl_stat *dbstat);
```

Initialization:

```
...
struct cl_stat dbstat;

memset(&dbstat, 0, sizeof(struct cl_stat));
cl_statinidir(dbdir, &dbstat);
```

To check for a change you just need to call `cl_statchkdir` and check its return value:

```
if(cl_statchkdir(&dbstat) == 1) {
    reload_database...;
    cl_statfree(&dbstat);
    cl_statinidir(cl_retdbdir(), &dbstat);
}
```

Remember to reset the `cl_stat` structure after reload.

6.5.1 Data scan functions

It's possible to scan a file or descriptor using:

```
int cl_scanfile(const char *filename, const char **virname,
unsigned long int *scanned, const struct cl_engine *engine,
const struct cl_limits *limits, unsigned int options);
```

```
int cl_scandesc(int desc, const char **virname, unsigned
long int *scanned, const struct cl_engine *engine, const
struct cl_limits *limits, unsigned int options);
```

Both functions will save a virus name under the pointer `virname`, the virus name is part of the engine structure and must not be released directly. If the third argument (`scanned`) is not `NULL`, the functions will increase its value with the size of scanned data (in `CL_COUNT_PRECISION` units). Both functions have support for archive limits in order to protect against Denial of Service attacks.

```
struct cl_limits {
    unsigned int maxreclevel;    /* maximum recursion level for archives */
    unsigned int maxfiles;      /* maximum number of files to be scanned
                                * within a single archive
                                */
    unsigned int maxmailrec;    /* maximum recursion level for mail files */
    unsigned int maxratio;     /* maximum compression ratio */
    unsigned long int maxfilesize; /* compressed files larger than this limit
                                * will not be scanned
                                */
    unsigned short archivememlim; /* limit memory usage for some unpackers */
};
```

The last argument (`options`) configures the scan engine and supports the following flags (that can be combined using bit operators):

- **CL_SCAN_STDOPT**
This is an alias for a recommended set of scan options. You should use it to make your software ready for new features in the future versions of `libclamav`.
- **CL_SCAN_RAW**
Use it alone if you want to disable support for special files.

- **CL_SCAN_ARCHIVE**
This flag enables transparent scanning of various archive formats.
- **CL_SCAN_BLOCKENCRYPTED**
With this flag the library will mark encrypted archives as viruses (Encrypted.Zip, Encrypted.RAR).
- **CL_SCAN_BLOCKMAX**
Mark archives as viruses if `maxfiles`, `maxfilesize`, or `maxrecllevel` limit is reached.
- **CL_SCAN_MAIL**
Enable support for mail files.
- **CL_SCAN_MAILURL**
The mail scanner will download and scan URLs listed in a mail body. This flag should not be used on loaded servers. Due to potential problems please do not enable it by default but make it optional.
- **CL_SCAN_OLE2**
Enables support for OLE2 containers (used by MS Office and .msi files).
- **CL_SCAN_PDF**
Enables scanning within PDF files.
- **CL_SCAN_PE**
This flag enables deep scanning of Portable Executable files and allows libclamav to unpack executables compressed with run-time unpackers.
- **CL_SCAN_ELF**
Enable support for ELF files.
- **CL_SCAN_BLOCKBROKEN**
libclamav will try to detect broken executables and mark them as Broken.Executable.
- **CL_SCAN_HTML**
This flag enables HTML normalisation (including ScrEnc decryption).
- **CL_SCAN_ALGORITHMIC**
Enable algorithmic detection of viruses.
- **CL_SCAN_PHISHING_DOMAINLIST**
Phishing module: restrict URL scanning to domains from .pdf (RECOMMENDED).

- **CL_SCAN_PHISHING_BLOCKSSL**
Phishing module: always block SSL mismatches in URLs.
- **CL_SCAN_PHISHING_BLOCKCLOAK**
Phishing module: always block cloaked URLs.

All functions return 0 (CL_CLEAN) when the file seems clean, CL_VIRUS when a virus is detected and another value on failure.

```

...
struct cl_limits limits;
const char *virname;

memset(&limits, 0, sizeof(struct cl_limits));
limits.maxfiles = 1000; /* max files */
limits.maxfilesize = 10 * 1048576; /* maximum size of archived or
                                   * compressed file (files exceeding
                                   * this limit will be ignored)
                                   */
limits.maxrecllevel = 5; /* maximum recursion level for archives */
limits.maxmailrec = 64; /* maximum recursion level for mail files */
limits.maxratio = 200; /* maximum compression ratio */

if((ret = cl_scanfile("/tmp/test.exe", &virname, NULL, engine,
&limits, CL_STDOPT)) == CL_VIRUS) {
    printf("Virus detected: %s\n", virname);
} else {
    printf("No virus detected.\n");
    if(ret != CL_CLEAN)
        printf("Error: %s\n", cl_strerror(ret));
}

```

6.5.2 Memory

Because the engine structure consumes a few megabytes of system memory, you should release it with `cl_free` if you no longer need to scan files.

6.5.3 clamav-config

Use `clamav-config` to check compilation information for `libclamav`.

```
zolw@localhost:~$ clamav-config --libs
-L/usr/local/lib -lz -lbz2 -lgmp -lpthread
zolw@localhost:~$ clamav-config --cflags
-I/usr/local/include -g -O2
```

6.5.4 Example

You will find an example scanner application in the clamav sources (/example). Don't forget that all programs based on libclamav must be linked against it:

```
gcc -Wall ex1.c -o ex1 -lclamav
```

6.6 CVD format

CVD (ClamAV Virus Database) is a digitally signed tarball containing one or more databases. The header is a 512-bytes long string with colon separated fields:

```
ClamAV-VDB:build time:version:number of signatures:functionality
level required:MD5 checksum:digital signature:builder name:build time (sec)
```

sigtool --info displays detailed information on CVD files:

```
zolw@localhost:/usr/local/share/clamav$ sigtool -i daily.cvd
Build time: 11 Feb 2007 19-28 +0000
Version: 2553
# of signatures: 6063
Functionality level: 9
Builder: ccordes
D5: 7f337b409249e11dea3effb04dd352f2
Digital signature: 6Ybd2eeDHBAs8raaEwmayqzoa5ysGDNnQ5Cc89mS2VCm1jRXZP
ke/itmTyYQTc/rgJc2uQPr+NvzvUxRpsniwoyZ/gIkPniCLnqVCY00ytwmirivbrV8j
0kzxb9nHd+5UQqj/Z3rLbS7T5HCbRX3uE0JX1tAo642Gq9ACH9Fc
Verification OK.
```

6.7 Contributors

The following people contributed to our project in some way (providing patches, bug reports, technical support, documentation, good ideas...):

- Ian Abbott <abbotti*mev.co.uk>
- Clint Adams <schizo*debian.org>
- Sergey Y. Afonin <asy*kraft-s.ru>
- Robert Allerstorfer <roal*anet.at>
- Claudio Alonso <cfalonso*yahoo.com>
- Kevin Amarin <kamarin*ccs.neu.edu>
- Kamil Andrusz <wizz*mniam.net>
- Tayfun Asker <tasker*metu.edu.tr>
- Jean-Edouard Babin <Jeb*jeb.com.fr>
- Marc Baudoïn <babafou*babafou.eu.org>
- Scott Beck <sbeck*gossamer-threads.com>
- Rolf Eike Beer <eike*mail.math.uni-mannheim.de>
- Rene Bellora <rbellora*tecnoaccion.com.ar>
- Carlo Marcelo Arenas Belon <carenas*sajinet.com.pe>
- Joseph Benden <joe*thrallingpenguin.com>
- Hilko Bengen <bengen*vdst-ka.inka.de>
- Hank Beatty <hbeatty*starband.net>
- Alexandre Biancalana <ale*seudns.net>
- Patrick Bihan-Faou <patrick*mindstep.com>
- Martin Blapp <mb*imp.ch>
- Dale Blount <dale*velocity.net>
- Serge van den Boom <svdb*stack.nl>
- Oliver Brandmueller <ob*e-Gitt.NET>
- Boguslaw Brandys <brandys*o2.pl>
- Igor Brezac <igor*ipass.net>

- Mike Brudenell <pmb1*york.ac.uk>
- Brian Bruns <bruns*2mbit.com>
- Len Budney <lbudney*pobox.com>
- Matt Butt <mattb*cre8tiv.com>
- Christopher X. Candrea <chris*westnet.com>
- Eric I. Lopez Carreon <elopezc*technitrade.com>
- Ales Casar <casar*uni-mb.si>
- Jonathan Chen <jon+clamav*spock.org>
- Andrey Cherezov <andrey*cherezov.koenig.su>
- Alex Cherney <alex*cher.id.au>
- Tom G. Christensen <tgc*statsbiblioteket.dk>
- Nicholas Chua <nicholas*ncmbox.net>
- Chris Conn <cconn*abacom.com>
- Christoph Cordes <ib*precompiled.de>
- Ole Craig <olc*cs.umass.edu>
- Eugene Crosser <crosser*rol.ru>
- Calin A. Culianu <calin*ajvar.org>
- Damien Curtain <damien*pagefault.org>
- Krisztian Czako <slapic*linux.co.hu>
- Diego d'Ambra <da*softcom.dk>
- Michael Dankov <misha*btrc.ru>
- Yuri Dario <mc6530*mclink.it>
- David <djgardner*users.sourceforge.net>
- Maxim Dounin <mdounin*rambler-co.ru>
- Alejandro Dubrovsky <s328940*student.uq.edu.au>

- James P. Dugal <jpd*louisiana.edu>
- Magnus Ekdahl <magnus*debian.org>
- Mehmet Ekiz <ekizm*tbmm.gov.tr>
- Jens Elkner <elkner*linofee.org>
- Fred van Engen <fred*wooha.org>
- Jason Englander <jason*englanders.cc>
- Oden Eriksson <oeriksson*mandrakesoft.com>
- Daniel Fahlgren <fahlgren*ardendo.se>
- Andy Fiddaman <af*jeamland.org>
- Edison Figueira Junior <edison*brc.com.br>
- David Ford <david+cert*blue-labs.org>
- Martin Forssen <maf*appgate.com>
- Brian J. France <list*firehawksystems.com>
- Free Oscar <freeoscar*wp.pl>
- Martin Fuxa <yeti*email.cz>
- Piotr Gackiewicz <gacek*intertele.pl>
- Jeremy Garcia <jeremy*linuxquestions.org>
- Dean Gaudet <dean-clamav*arctic.org>
- Michel Gaudet <Michel.Gaudet*ehess.fr>
- Philippe Gay <ph.gay*free.fr>
- Nick Gazaloff <nick*sbin.org>
- Geoff Gibbs <ggibbs*hgmp.mrc.ac.uk>
- Luca 'NERvOus' Gibelli <nervous*nervous.it>
- Scott Gifford <sgifford*suspectclass.com>
- Wieslaw Glod <>wkg*x2.pl>

- Stephen Gran <steve*lobefin.net>
- Koryn Grant <koryn*endace.com>
- Matthew A. Grant <grantma*anathoth.gen.nz>
- Christophe Grenier <grenier*cgsecurity.org>
- Marek Gutkowski <hobbit*core.segfault.pl>
- Jason Haar <Jason.Haar*trimble.co.nz>
- Hrvoje Habjanic <hrvoje.habjanic*zg.hinet.hr>
- Michal Hajduczenia <michalis*mat.uni.torun.pl>
- Jean-Christophe Heger <jcheger*acytec.com>
- Martin Heinz <Martin*hemag.ch>
- Kevin Heneveld” <kevin*northstar.k12.ak.us>
- Anders Herbjornsen <andersh*gar.no>
- Paul Hoadley <paulh*logixsquad.net>
- Robert Hogan <robert*roberthogan.net>
- Przemyslaw Holowczyc <doozer*skc.com.pl>
- Thomas W. Holt Jr. <twh*cohesive.net>
- James F. Hranicky <jfh*cise.ufl.edu>
- Douglas J Hunley <doug*hunley.homeip.net>
- Kurt Huwig <kurt*iku-netz.de>
- Andy Igoshin <ai*vsu.ru>
- Michal Jaegermann <michal*harddata.com>
- Christophe Jaillet <christophe.jaillet*wanadoo.fr>
- Jay <sysop-clamav*coronastreet.net>
- Stephane Jeannenot <stephane.jeannenot*wanadoo.fr>
- Per Jessen <per*computer.org>

- Dave Jones <dave*kalkbay.co.za>
- Jesper Juhl <juhl*dif.dk>
- Kamil Kaczowski <kamil*kamil.eisp.pl>
- Alex Kah <alex*narfonix.com>
- Stefan Kaltenbrunner <stefan*kaltenbrunner.cc>
- Lloyd Kamara <l.kamara*imperial.ac.uk>
- Stefan Kanthak <stefan.kanthak*fujitsu-siemens.com>
- Kazuhiko <kazuhiko*fdiary.net>
- Jeremy Kitchen <kitchen*scriptkitchen.com>
- Tomasz Klim <tomek*euroneto.pl>
- Robbert Kouprie <robbert*exx.nl>
- Martin Kraft <martin.kraft*fal.de>
- Petr Kristof <Kristof.P*fce.vutbr.cz>
- Henk Kuipers <henk*opensourceolutions.nl>
- Nigel Kukard <nkukard*lbsd.net>
- Eugene Kurmanin <smfs*users.sourceforge.net>
- Dr Andrzej Kurpiel <akurpiel*mat.uni.torun.pl>
- Mark Kushinsky <mark*mdspc.com>
- Mike Lambert <lambert*jeol.com>
- Thomas Lamy <Thomas.Lamy*in-online.net>
- Stephane Leclerc <sleclerc*aliastec.net>
- Marty Lee <marty*maui.co.uk>
- Dennis Leeuw <dleeuw*made-it.com>
- Martin Lesser <admin-debian*bettercom.de>
- Peter N Lewis <peter*stairways.com.au>

- Matt Leyda <mfleyda*e-one.com>
- James Lick <jlick*drivel.com>
- Jerome Limozin <jerome*limozin.net>
- Mike Loewen <mloewen*sturgeon.cac.psu.edu>
- Roger Lucas <roger*planbit.co.uk>
- David Luyer <david_luyer*pacific.net.au>
- Richard Lyons <frob-clamav*webcentral.com.au>
- David S. Madole <david*madole.net>
- Thomas Madsen <tm*softcom.dk>
- Bill Maidment <bill*maidment.com.au>
- Joe Maimon <jmaimon*ttec.com>
- David Majorel <dm*lagoon.nc>
- Andrey V. Malyshev <amal*krasn.ru>
- Fukuda Manabu <fukuda*cri-mw.co.jp>
- Stefan Martig <sm*officeco.ch>
- Alexander Marx <mad-ml*madness.at>
- Andreas Marx (<http://www.av-test.org/>)
- Chris Masters <cmasters*inssl.co.uk>
- Fletcher Mattox <fletcher*cs.utexas.edu>
- Serhiy V. Matveyev <matveyev*uatele.com>
- Reinhard Max <max*suse.de>
- Brian May <bam*debian.org>
- Ken McKittrick <klmac*usadatanet.com>
- Chris van Meerendonk <cvm*castel.nl>
- Andrey J. Melnikoff <temnota*kmv.ru>

- Damian Menscher <menscher*uiuc.edu>
- Denis De Messemaeker <ddm*clamav.net>
- Jasper Metselaar <jasper*formmailer.net>
- Arkadiusz Miskiewicz <misiek*pld-linux.org>
- Ted Mittelstaedt <tedm*toybox.placo.com>
- Mark Mielke <mark*mark.mielke.cc>
- John Miller <contact*glideslopesoftware.co.uk>
- Jo Mills <Jonathan.Mills*frequentis.com>
- Dustin Mollo <dustin.mollo*sonoma.edu>
- Remi Mommsen <remigius.mommsen*cern.ch>
- Doug Monroe <doug*planetconnect.com>
- Alex S Moore <asmooore*edge.net>
- Tim Morgan <tim*sentinelchicken.org>
- Dirk Mueller <mueller*kde.org>
- Flinn Mueller <flinn*activeintra.net>
- Hendrik Muhs <Hendrik.Muhs*student.uni-magdeburg.de>
- Simon Munton <simon*munton.demon.co.uk>
- Farit Nabiullin (<http://program.farit.ru/>)
- Nemosoft Unv. <nemosoft*smcc.demon.nl>
- Wojciech Noworyta <wnow*konarski.edu.pl>
- Jorgen Norgaard <jnp*anneli.dk>
- Fajar A. Nugraha <fajar*telkom.co.id>
- Joe Oaks <joe.oaks*hp.com>
- Washington Odhiambo <wash*wananchi.com>
- Masaki Ogawa <proc*mac.com>

- John Ogness <jogness*antivir.de>
- Phil Oleson <oz*nixil.net>
- Jan Ondrej <ondrej*salstar.sk>
- Martijn van Oosterhout <kleptog*svana.org>
- OpenAntiVirus Team (<http://www.OpenAntiVirus.org/>)
- Tomasz Papszun <tomek*lodz.tpsa.pl>
- Eric Parsonage <eric*eparsonage.com>
- Oliver Paukstadt <pstadt*stud.fh-heilbronn.de>
- Christian Pelissier <Christian.Pelissier*onera.fr>
- Rudolph Pereira <rudolph*usyd.edu.au>
- Dennis Peterson <dennispe*inetnw.com>
- Ed Phillips <ed*UDel.Edu>
- Andreas Piesk <Andreas.Piesk*heise.de>
- Mark Pizzolato <clamav-devel*subscriptions.pizzolato.net>
- Dean Plant <dean.plant*roke.co.uk>
- Alex Pleiner <pleiner*zeitform.de>
- Ant La Porte <ant*dvere.net>
- Jef Poskanzer <jef*acme.com>
- Christophe Poujol <Christophe.Poujol*atosorigin.com>
- Sergei Pronin <sp*finndesign.fi>
- Thomas Quinot <thomas*cuivre.fr.eu.org>
- Ed Ravin <eravin*panix.com>
- Robert Rebbun <robert*desertsurf.com>
- Brian A. Reiter <breiter*wolfereiter.com>
- Didi Rieder <adrieder*sbox.tugraz.at>

- Pavel V. Rochnyack <rpv*fsf.tsu.ru>
- Rupert Roesler-Schmidt <r.roesler-schmidt*uplink.at>
- David Sanchez <dsanchez*veloxia.com>
- David Santinoli <david*santinoli.com>
- Vijay Sarvepalli <vssarvep*office.uncg.edu>
- Martin Schitter
- Theo Schlossnagle <jesus*omniti.com>
- Enrico Scholz <enrico.scholz*informatik.tu-chemnitz.de>
- Karina Schwarz <k.schwarz*uplink.at>
- Scsi <scsi*softland.ru>
- Dr Matthew J Seaman <m.seaman*infracaninophile.co.uk>
- Hector M. Rulot Segovia <Hector.Rulot*uv.es>
- Omer Faruk Sen <ofsen*enderunix.org>
- Sergey <a_s_y*sama.ru>
- Tuomas Silen <tuomas.silen*nodeta.fi>
- David F. Skoll <dfs*roaringpenguin.com>
- Al Smith <ajs+clamav*aeschi.ch.eu.org>
- Sergey Smitienko <hunter*comsys.com.ua>
- Solar Designer <solar*openwall.com>
- Joerg Sonnenberger <joerg*britannica.bec.de>
- Michal 'GiM' Spadlinski (<http://gim.org.pl/>)
- Kevin Spicer <kevin*kevinspicer.co.uk>
- GertJan Spoelman <cav*gjs.cc>
- Ole Stanstrup <ole*stanstrup.dk>
- Adam Stein <adam*scan.mc.xerox.com>

- Steve <steveb*webtribe.net>
- Richard Stevenson <richard*endace.com>
- Sven Strickroth <sstrickroth*gym-oha.de>
- Matt Sullivan <matt*sullivan.gen.nz>
- Dr Zbigniew Szewczak <zssz*mat.uni.torun.pl>
- Joe Talbott <joseph*t*cstone.net>
- Gernot Tenchio <g.tenchio*telco-tech.de>
- Masahiro Teramoto <markun*onohara.to>
- Daniel Theodoro <dtheodoro*ig.com.br>
- Ryan Thompson <clamav*sasknow.com>
- Gianluigi Tiesi <sherpya*netfarm.it>
- Yar Tikhii <yar*comp.chem.msu.su>
- Andrew Toller <atoller*connectfree.co.uk>
- Michael L. Torrie <torriem*chem.byu.edu>
- Trashware <trashware*gmx.net>
- Matthew Trent <mtrent*localaccess.com>
- Reini Urban <rurban*x-ray.at>
- Daniel Mario Vega <dv5a*dc.uba.ar>
- Denis Vlasenko <vda*ilport.com.ua>
- Laurent Wacrenier <lwa*teaser.fr>
- Charlie Watts <cewatts*brainstorminternet.net>
- Florian Weimer <fw*deneb.enyo.de>
- Paul Welsh <paul*welshfamily.com>
- Nicklaus Wicker <n.wicker*cnk-networks.de>
- David Woakes <david*mitredata.co.uk>

- Troy Wollenslegel <troy*intranet.org>
- ST Wong <st-wong*cuhk.edu.hk>
- Dale Woolridge <dwoolridge*drh.net>
- David Wu <dyw*iohk.com>
- Takumi Yamane <yamtak*b-session.com>
- Youza Youzovic <youza*post.cz>
- Anton Yuzhaninov <citrin*rambler-co.ru>
- Leonid Zeitlin <lz*europa.com>
- ZMan Z. <x86zman*go-a-way.dyndns.org>
- Andoni Zubimendi <andoni*lpsat.net>

6.8 Donors

We've received financial support from: (in alphabetical order)

- ActiveIntra.net Inc. (<http://www.activeintra.net/>)
- Advance Healthcare Group (<http://www.ahgl.com.au/>)
- Allied Quotes (<http://www.AlliedQuotes.com/>)
- American Computer & Electronic Services Corp. (<http://www.acesnw.com/>)
- Amnesty International, Swiss Section (<http://www.amnesty.ch/>)
- Steve Anderson
- Anonymous donor from Colorado, US
- Arudius (<http://arudius.sourceforge.net/>)
- Peter Ashman
- Atlas College (<http://www.atlascollege.nl/>)
- Australian Payday Cash Loans (<http://www.cashdoctors.com.au/>)
- AWD Online (<http://www.awdonline.com/>)

- BackupAssist Backup Software (<http://www.backupassist.com/>)
- Dave Baker
- Bear and Bear Consulting, Inc. (<http://www.bear-consulting.com/>)
- Aaron Begley
- Craig H. Block
- Norman E. Brake, Jr.
- Josh Burstyn
- By Design (<http://www.by-design.net/>)
- Canadian Web Hosting (<http://www.canadianwebhosting.com/>)
- cedar creek software.com (<http://www.cedarcreeksoftware.com/>)
- Ricardo Cerqueira
- Thanos Chatziathanassiou
- Cheahch from Singapore
- Conexim Australia - business web hosting (<http://www.conexim.com.au>)
- Alan Cook
- Joe Cooper
- CustomLogic LLC (<http://www.customlogic.com/>)
- Ron DeFulio
- Digirati (<http://oss.digirati.com.br/>)
- Steve Donegan (<http://www.donegan.org/>)
- Dynamic Network Services, Inc (<http://www.dyndns.org/>)
- EAS Enterprises LLC
- eCoupons.com (<http://www.ecoupons.com/>)
- Electric Embers (<http://electricembers.net>)
- John T. Ellis

- Epublica
- Bernhard Erdmann
- David Eriksson (<http://www.2good.nu/>)
- Philip Ershler
- Explido Software USA Inc. (<http://www.explido.us/>)
- David Farrick
- Jim Feldman
- Petr Ferschmann (<http://petr.ferschmann.cz/>)
- Andries Filmer (<http://www.netexpo.nl/>)
- The Free Shopping Cart people (<http://www.precisionweb.net/>)
- Paul Freeman
- Jack Fung
- Stephen Gageby
- Paolo Galeazzi
- GANDI (<http://www.gandi.net/>)
- Jeremy Garcia (<http://www.linuxquestions.org/>)
- GBC Internet Service Center GmbH (<http://www.gbc.net/>)
- GCS Tech (<http://www.gcstech.net/>)
- GHRS (<http://www.ghrshotels.com/>)
- Lyle Giese
- Todd Goodman
- Bill Gradwohl (<http://www.ycc.com/>)
- Grain-of-Salt Consulting
- Terje Gravvold
- Hart Computer (<http://www.hart.co.jp/>)

- Pen Helm
- Hosting Metro LLC (<http://www.hostingmetro.com/>)
- IDEAL Software GmbH (<http://www.IdealSoftware.com/>)
- Industry Standard Computers (<http://www.ISCnetwork.com/>)
- Interact2Day (<http://www.interact2day.com/>)
- Invisik Corporation (<http://www.invisik.com/>)
- itXcel Internet - Domain Registration (<http://www.itxcel.com>)
- Craig Jackson
- Stuart Jones
- Jason Judge
- Keith (<http://www.textpad.com/>)
- Ewald Kicker (<http://www.very-clever.com/>)
- Brad Koehn
- Christina Kuratli (<http://www.virusprotect.ch/>)
- Logic Partners Inc. (<http://www.logicpartners.com/>)
- Mark Lotspaih (<http://www.lotcom.org/>)
- Michel Machado (<http://oss.digirati.com.br/>)
- Olivier Marechal
- Matthew McKenzie
- Durval Menezes (<http://www.durval.com.br/>)
- Micro Logic Systems (<http://www.mls.nc/>)
- Midcoast Internet Solutions
- Mimecast (<http://www.mimecast.com/>)
- Kazuhiro Miyaji
- Bozidar Mladenovic

- Paul Morgan
- Tomas Morkus
- The Names Database (<http://static.namesdatabase.com>)
- Names Directory (<http://www.namesdir.com/>)
- Michael Nolan (<http://www.michaelnolan.co.uk/>)
- Jorgen Norgaard
- Numedeon, Inc. creators of Whyville (<http://www.whyville.net/>)
- Oneworkspace.com (<http://www.oneworkspace.com/>)
- Online Literature (<http://www.couol.com/>)
- Origin Solutions (<http://www.originsolutions.com.au/>)
- outermedia GmbH (<http://www.outermedia.de/>)
- Kevin Pang (<http://www.freebsdblog.org/>)
- Alexander Panzhin
- Passageway Communications (<http://www.passageway.com>)
- Dan Pelleg (<http://www.libagent.org/>)
- Thodoris Pitikaris
- Paul Rantin
- Thomas J. Raef (<http://www.ebasedsecurity.com>)
- Luke Reeves (<http://www.neuro-tech.net/>)
- RHX (<http://www.rhx.it/>)
- Stefano Rizzetto
- Roaring Penguin Software Inc. (<http://www.roaringpenguin.com/>)
- Luke Rosenthal
- Jenny Sfstrm (<http://PokerListings.com>)

- School of Engineering, University of Pennsylvania (<http://www.seas.upenn.edu/>)
- Tim Scoff
- Seattle Server (<http://www.seattleserver.com/>)
- Software Workshop Inc (<http://www.softwareworkshop.com/>)
- Solutions In A Box (<http://www.siab.com.au/>)
- Stephane Rault
- SearchMain (<http://www.searchmain.com/>)
- Olivier Silber
- Fernando Augusto Medeiros Silva (<http://www.linuxplace.com.br/>)
- Sollentuna Fria Gymnasium, Sweden (<http://www.sfg.se/>)
- StarBand (<http://www.starband.com/>)
- Stroke of Color, Inc.
- Synchro Sistemas de Informacao (<http://synchro.com.br/>)
- Sahil Tandon
- The Spamex Disposable Email Address Service (<http://www.spamex.com>)
- Brad Tarver
- TGT Tampermeier & Grill Steuerberatungs- und Wirtschaftstreuhand OEG (<http://www.tgt.at/>)
- Per Reedtz Thomsen
- William Tisdale
- Up Time Technology (<http://www.uptimetech.com/>)
- Ulfi
- Jeremy Vanderburg (<http://www.jeremytech.com/>)
- Web.arbyte - Online-Marketing (<http://www.webarbyte.de/>)

- Webzone Srl (<http://www.webzone.it/>)
- Markus Welsch (<http://www.linux-corner.net/>)
- Julia White (<http://www.convert-tools.com/>)
- Nicklaus Wicker
- David Williams (<http://kayakero.net/>)
- Glenn R Williams
- Kelly Williams
- XRoads Networks (<http://xroadsnetworks.com/>)
- Zimbra open-source collaboration suite (<http://www.zimbra.com/>)

6.9 Graphics

The ClamAV logo was created by Mia Kalenius and Sergei Pronin from Finndesign (<http://www.finndesign.fi/>).

6.10 OpenAntiVirus

Our database includes the virus database (about 7000 signatures) from OpenAntiVirus (<http://OpenAntiVirus.org>).

7 Core Team

- aCaB <acab*clamav.net>, Italy
Role: virus database maintainer, coder
- Mike Cathey <mike*clamav.net>, USA
Role: co-sysadmin
- Christoph Cordes <ccordes*clamav.net>, Germany
Role: virus database maintainer
- Diego d'Ambra <diego*clamav.net>, Denmark
Role: virus database maintainer
- Luca Gibelli <luca*clamav.net>, Italy
Role: sysadmin, mirror coordinator

- Nigel Horne <njh*clamav.net>, United Kingdom
Role: coder
- Arnaud Jacques <arnaud*clamav.net>, France
Role: virus database maintainer
- Tomasz Kojm <tkojm*clamav.net>, Poland
Role: project leader, coder
- Tomasz Papszun <tomek*clamav.net>, Poland
Role: various help
- Sven Strickroth <sven*clamav.net>, Germany
Role: virus database maintainer, virus submission management
- Edwin Torok <edwin*clamav.net>, Romania
Role: coder
- Trog <trog*clamav.net>, United Kingdom
Role: coder