

Creating signatures for ClamAV

1 Introduction

CVD (ClamAV Virus Database) is a digitally signed tarball file that contains one or more databases. The header is a 512 bytes long string with colon separated fields:

```
ClamAV-VDB:build time:version:number of signatures:functionality
level required:MD5 checksum:digital signature:builder name:build
time (sec)
```

`sigtool --info` displays detailed information on CVD files:

```
zolw@localhost:/usr/local/share/clamav$ sigtool -i daily.cvd
Build time: 11 Sep 2004 21-07 +0200
Version: 487
# of signatures: 1189
Functionality level: 2
Builder: ccordes
MD5: a3f4f98694229e461f17d2aa254e9a43
Digital signature: uwJS6d+y/9g5SXGE0Hh1rXyjZW/PGK/zqVtWWVL3/
tfHEnA17z6VB2IBR2I/OitKRYzmVo3ibU7bPCJNgi6fPcW1PQwvCunwAswvR
0ehrvY/4ksUjUOXo1VwQlW7l86HZmiMUSyAjnF/gciOSsOQa9Hli8D5uET1RD
zVpoWu/id
Verification OK.
```

There are two CVD databases in ClamAV: *main.cvd* and *daily.cvd* for daily updates.

2 MD5 signatures

There's an easy way to create signatures for static malware using MD5 checksums. To create a signature for `test.exe` use the `--md5` option of `sigtool`:

```
zolw@localhost:/tmp/test$ sigtool --md5 test.exe > test.hdb
zolw@localhost:/tmp/test$ cat test.hdb
48c4533230e1ae1c118c741c0db19dfb:17387:test.exe
```

That's it! The signature is ready to use:

```
zolw@localhost:/tmp/test$ clamscan -d test.hdb test.exe
test.exe: test.exe FOUND
```

```
----- SCAN SUMMARY -----
Known viruses: 1
Scanned directories: 0
Scanned files: 1
Infected files: 1
Data scanned: 0.02 MB
I/O buffer size: 131072 bytes
Time: 0.024 sec (0 m 0 s)
```

You can edit it to change the name (by default sigtool uses the file name). Remember that all MD5 signatures must be placed in *.hdb files, you can include any number of sigs in a file. To get them automatically loaded every time clamscan/clamd starts just copy them to the local virus database directory.

3 Hexadecimal signatures

ClamAV keeps viral fragments in hexadecimal format. If you don't know how to get a proper signature please try the MD5 method or submit your sample on <http://www.clamav.net/sendvirus.html>.

3.1 Hexadecimal format

You can use sigtool --hex-dump to convert arbitrary data into hexadecimal format:

```
zolw@localhost:/tmp/test$ sigtool --hex-dump
How do I look in hex?
486f7720646f2049206c6f6f6b20696e206865783f0a
```

3.2 Wildcards

ClamAV supports the following extensions in hex signatures:

- ??
Match any byte.
- *
Match any number of bytes.
- {n}
Match n bytes.
- {-n}
Match n or less bytes.
- {n-}
Match n or more bytes.
- (a|b)
Match a and b (you can use more alternate characters).

3.3 Basic signature format

The simplest signatures are of the format:

```
MalwareName=HexSignature
```

ClamAV will analyse a whole content of a file trying to match it. All signatures of this type must be placed in *.db files.

3.4 Extended signature format

Extended signature format allows target type and offset specification. The format is:

```
MalwareName:TargetType:Offset:HexSignature
```

where TargetType is a decimal number describing a target type:

- 0 = any file
- 1 = Portable Executable

- 2 = OLE2 component (e.g. VBA script)
- 3 = HTML (normalised)
- 4 = Mail file
- 5 = Graphics (to help catching exploits in JPEG files)

And `Offset` is an asterisk or a decimal number `n` possibly combined with a special string:

- `*` = any
- `n` = absolute offset
- `EOF-n` = end of file minus `n` bytes

Signatures for Portable Executables files (target = 1) also support:

- `EP+n` = entry point plus `n` bytes (`EP+0` if you want to anchor to `EP`)
- `Sx+n` = start of section's `x` (counted from 0) data plus `n` bytes

All signatures in the extended format must be placed in `*.ndb` files.

3.5 Signature names

ClamAV uses the following prefixes for particular malware:

- *Worm* for Internet worms
- *Trojan* for backdoor programs
- *JS* for Java Script malware
- *VBS* for VBS malware
- *W97M*, *W2000M* for Word macro viruses
- *X97M*, *X2000M* for Excel macro viruses
- *O97M*, *O2000M* for general Office macro viruses
- *DoS* for Denial of Service attack software
- *Exploit* for popular exploits
- *VirTool* for virus construction kits
- *Dialer* for dialers
- *Joke* for hoaxes

4 Special files

4.1 HTML

ClamAV contains a special HTML normalisation code required to detect HTML exploits. Running `sigtool --html-normalise` on a HTML file will produce the following files:

- `comment.html` - the whole file normalised
- `nocomment.html` - the file normalised, with all comments removed
- `script.html` - the parts of the file in `<script>` tags (lowercased)

The code automatically decodes `JScript.encode` parts and char ref's (e.g. `f`). You need to create a signature against one of the created files. To eliminate potential false positive alerts you should use extended signature format with target type of 3.

4.2 Compressed Portable Executable files

If the file is compressed with UPX, FSG, or Petite run `clamscan` with `--debug` and `--leave-temps`. Example output on FSG compressed file:

```
LibClamAV debug: UPX/FSG: empty section found - assuming compression
LibClamAV debug: FSG: found old EP @1554
LibClamAV debug: FSG: Successfully decompressed
LibClamAV debug: UPX/FSG: Decompressed data saved in /tmp/clamav-4eba73ff4050a26
```

And create a signature for `/tmp/clamav-4eba73ff4050a26`

5 Building CVD files - ClamAV maintainers only

Run `freshclam` to check you're using the latest databases. Next go to some **empty** temporary directory and execute the following command:

```
sigtool --unpack-current daily.cvd
```

This will unpack all databases from the current *daily.cvd* database. Add signatures to appropriate files and build the final CVD:

```
sigtool --build daily.cvd --server SIGNING_SERVER
```

where `SIGNING_SERVER` is one of the ClamAV Signing Servers you have access to. This command will automatically generate binary database with a digital signature.

```
LibClamAV debug: Loading databases from .
LibClamAV debug: Loading ./daily.db
LibClamAV debug: Loading ./daily.hdb
LibClamAV debug: Initializing trie.
Database properly parsed.
Signatures: 183
COPYING
tar: main.db: Cannot stat: No such file or directory
tar: main.hdb: Cannot stat: No such file or directory
daily.db
daily.hdb
tar: Notes: Cannot stat: No such file or directory
tar: Error exit delayed from previous errors
Builder id: tkojm
Password:
Signature received (length = 171).
Database daily.cvd created.
```

Don't worry about "No such file or directory" *tar* errors. Finally, you can verify the new database with:

```
zolw@localhost:/usr/local/share/clamav$ sigtool -i daily.cvd
Build time: 26 Aug 2004 22:41 +0200
Version: 473
# of signatures: 183
Functionality level: 2
Builder: tkojm
MD5: 0e89235392c1a1142dda0d022f218903
Digital signature: bWBCx3K07rkd0Qo+zTIZXKhGNvmEz5n/ftUsCEVrdFwhW
r2gf5MjSm07nF/4BdRV/qwXEHJtp0i/2g6awhqUFa073bbH5f+zmuHy8h0wqYv6j
hlIdeA8uh6DGQYBj7azyS90/0+bXEvU1SutpL3rW8ireFky6zXKv5BVbhnZj9j
Verification OK.
```

Now you must update the main rsync server:

```
rsync -tcz --stats --progress -e ssh daily.cvd clamupload@rsync1.clamav.net:public_html/  
ssh rsync1.clamav.net -i ~/.ssh/id_rsa -l clamavdb sleep 1
```

Please consult [1] for more information. After an update please send a summary to clamav-virusdb@lists.sf.net. Thanks !

References

- [1] Luca Gibelli: *Mirroring the Virus Database*
<http://www.clamav.net/doc/mirrors>